




CXV-D

Refrigerant condensers



Key benefits

- Star in energy efficiency
- Low maintenance and easy inspection
- Optimal performance guaranteed

CXV-D characteristics

- Counter flow, axial fan, induced draft
- PED/97/23/EC coil design

Capacity range

2750 - 4025 kW
(for single cell models, nominal R717 kW's)

Typical applications

- Very large industrial refrigeration and process projects
- Low energy requirements
- Low sound requirements



Star in energy efficiency

- [Evaporative cooling](#) PLUS unique [combined heat transfer system](#) for minimized system-wide energy consumption.
- **Axial fan** – half the consumption of rivals and huge single cell capacity: saving you more!
- [BACross II fill](#) factory-configured for unrivalled water/air contact and minimal air pressure drop. Guarantees **optimal condenser efficiency** with cooling system energy well under control.
- **High efficiency fan motors.**

Low maintenance and easy inspection

- Inspect and maintain towers with **unrivalled comfort and safely: while standing** inside.
- The CXV-D has a **spacious plenum** (internal area) and **easy inspection/maintenance access**.
- Inspect internal fill and coil easily via removable drift eliminator modules.
- The [BACross II fill](#) is telescopically-supported for easy sheet by sheet inspection/cleaning and **no dismantling**.
- **Fans** are easily accessible from the in- and outside
- Self-cleaning cold water basin and fill above **sloped basin** to flush out dirt and debris.

Optimal performance guaranteed

- Unique and patented heat transfer system: **featuring [combined flow](#)** via heat exchange coil and fill pack, for fine temperature applications and thermal challenges.
- **Huge industry-best single cell capacity!**
- [BACross II fill](#) - patented sheet and **maximum air/water contact** for optimal heat transfer performance.
- Encased in **corrosion-resistant fibreglass** polyester for long service life.

Reduced refrigerant charge

- **Less coil surface** (because of the patented combined heat transfer system) means less refrigerant charge and reduced overall system costs.

Ultra silent design

- CXV-D units include **low noise axial fans** for minimal surrounding noise. To reduce noise even further, choose [Whisper Quiet fans](#).
- Factory designed, tested and rated [sound attenuation](#) is available on air inlet to cut operation noise even further.
- [BACross II fill](#) guides smoothly the water all the way into the basin **without water splash noise**.

Unmatched hygiene control



- Easy-clean and easy-inspect CXV-D condensers **reduce hygiene risks** from bacteria or biofilm inside.
- **Combined inlet shields** block sunlight to prevent biological growth in the tower, filter the air and stop water splashing outside.
- The **drift eliminators** tested to Eurovent standards to prevent droplets escaping into the air.

Cheap to install

- CXV-D condensers are factory-built and shipped in sections for larger models to reduce the overall size and weight, allowing **easy on-site section assembly** with smaller crane.
- **Fewer coil connections**, reduce costs of pipe, valves, purges and labour.

Interested in the CXV-D evaporative condenser for your industrial refrigeration application? Contact your local [BAC representative](#) for more information.

Downloads

- [CXV-D refrigerant condenser](#)
- [Operating and Maintenance CXV-D](#)
- [Rigging and installation CXV-D](#)