



# SP SpartiumCooler

Previous generation products



## Key benefits

- Cheaper to ship and install
- Water saving
- Top hygiene control

### SP SpartiumCooler characteristics

TrilliumSeries cooler  
Counter flow, adiabatic pre-cooling, axial fan, induced draft

### Capacity range

340 - 1560 kW

### Maximum entering fluid temperature

60°C

### Typical applications

- Small to medium HVAC and industrial applications
- Locations with limited water and space availability
- High temperature industrial applications



## Cheaper to ship and install

- SpartiumCoolers fit on **standard trucks**.
- **Pre-coolers are factory-installed** and small cranes are all you need to mount coolers on-site.

## Water saving

- SpartiumCoolers achieve **annual water savings exceeding 80% water** compared to normal cooling towers by limited adiabatic operation.

## Top hygiene control

- Featuring a **once-through system**: recirculation and stagnation of water eliminated.
- **No stagnant water**: pre-cooler water conveyed from pads to sewer via a gutter.
- **No aerosol formation**: SpartiumCoolers minimize the Legionella risk.
- SpartiumCoolers cool incoming air **without transferring water** to the dry coil.

## Boosting thermal performance

- Pads in front of the finned coil pre-cool air to **virtual wet bulb temperature**.
- **Up to 40% improved capacity** compared to dry cooling.
- SpartiumCoolers consume **less energy**
- SpartiumCoolers achieve **low process temperatures**.
- Try the cooler with **EC motor** and improve pre-cooler performance resulting in **lower sound levels** and **25% lower electrical consumption**.

Interested in the SpartiumCooler for cooling your process? Contact your local [BAC representative](#) for more information.

## Downloads

- [SP Spartiumcooler](#)
- [SP SpartiumCooler](#)
- [Operating and Maintenance SP](#)
- [Rigging and Installation SP SpartiumCooler](#)
- [Operating and Maintenance SP EC](#)
- [Rigging and installation SP EC](#)